

标准油路块 D07SP



型号说明

HY* D07 SP * * / 10

A 铝 7A04 最高压力20.7MPa
D 钢 45# 最高压力31.5MPa

16通径

过渡块

油口位置
SO 侧面油口
B 底面油口

设计序列号

P,A,B,T油口螺纹				X,Y油口螺纹	
12P	3/4"NPT(Z)	16P	1"NPT(Z)	1/4"NPT(Z)	
12S	SAE-12	16S	SAE-16	SAE-6	
12B	3/4"BSP(G)	16B	1"BSP(G)	1/4"BSP(G)	
12M	M27X2	16M	M33X2	M14X1.5	

外形尺寸

尺寸	A	B	C	D	E	F	G	H	I
D07SPSO12	1.75 [44.5]	3.75 [95.3]	4.75 [120.7]	2.34 [59.4]	0.38 [9.5]	4.38 [111.3]	1.88 [47.8]	2.69 [68.3]	0.81 [20.6]
D07SPST12	1.75 [44.5]	3.75 [95.3]	4.75 [120.7]	2.34 [59.4]	0.38 [9.5]	4.38 [111.3]	1.88 [47.8]	2.69 [68.3]	0.81 [20.6]
D07SPSO16	3.00 [76.2]	5.00 [127.0]	5.50 [139.7]	2.97 [75.4]	0.50 [12.7]	5.00 [127.0]	2.50 [63.5]	3.31 [84.2]	1.19 [30.2]
*D07SPB12B	1.50 [38.1]	4.00 [101.6]	4.75 [120.7]	2.34 [59.4]	0.38 [9.5]	4.37 [111.0]	2.00 [50.8]	2.81 [71.4]	1.09 [27.7]
*D07SPB12[M,P,S,T]	1.50 [38.1]	4.00 [101.6]	4.75 [120.7]	2.34 [59.4]	0.38 [9.5]	4.37 [111.0]	2.00 [50.8]	2.81 [71.4]	1.09 [27.7]
D07SPB16	2.75 [69.9]	5.00 [127.0]	6.00 [152.4]	2.97 [75.4]	0.50 [12.7]	5.50 [139.7]	2.50 [63.5]	3.31 [84.2]	1.25 [31.8]

标准油路块 D07SP

外形尺寸

旁路油口过渡块
阀安装螺纹:美制 0.25-20 x 0.75 DP 和 0.38-16 x 1.00 DP
公制 M6-1.0mm ISO 6H x [19.1] DP 和 M10-1.5mm ISO 6H x [25.4] DP

视图关系

底面油口过渡块
阀安装螺纹:美制 0.25-20 x 0.75 DP 和 0.38-16 x 1.00 DP
公制 M6-1.0mm ISO 6H x [19.1] DP 和 M10-1.5mm ISO 6H x [25.4] DP

尺寸	J	K	L	M	N	O	P	Q	R
D07SPSO12	1.50 [38.1]	3.13 [79.5]	1.19 [30.2]	2.78 [70.6]	1.25 [31.8]	1.12 [28.4]	2.62 [66.5]	---	---
D07SPST12	1.50 [38.1]	3.13 [79.5]	---	2.78 [70.6]	1.25 [31.8]	1.12 [28.4]	2.62 [66.5]	1.09 [27.7]	2.69 [68.3]
D07SPSO16	1.81 [46.0]	4.13 [104.8]	1.19 [30.2]	3.50 [88.9]	2.38 [60.3]	1.75 [44.5]	3.25 [82.6]	---	---
*D07SPB12B	2.75 [69.9]	4.00 [101.6]	1.19 [30.2]	2.81 [71.4]	4.09 [103.9]	1.13 [28.7]	2.94 [74.7]	1.13 [28.7]	2.94 [74.7]
*D07SPB12[M,P,S,T]	2.81 [71.4]	4.00 [101.6]	1.25 [31.8]	2.91 [73.9]	4.09 [103.9]	1.13 [28.7]	2.94 [74.7]	1.13 [28.7]	2.94 [74.7]
D07SPB16	3.50 [88.9]	5.31 [134.9]	1.38 [34.9]	3.63 [92.1]	5.31 [134.9]	1.38 [34.9]	3.63 [92.1]	1.63 [41.3]	3.44 [87.3]